



US 20170031256A1

(19) **United States**

(12) **Patent Application Publication**
LEE et al.

(10) **Pub. No.: US 2017/0031256 A1**

(43) **Pub. Date: Feb. 2, 2017**

(54) **METHOD OF PREPARING
POLY-SILICIC-FERRIC COAGULANT (PSFC)
FOR ELECTROSTATIC CHARGE IMAGE
DEVELOPING TONER**

(71) Applicant: **SAMSUNG ELECTRONICS CO.,
LTD.**, Suwon-si (KR)

(72) Inventors: **Sung-hwa LEE**, Suwon-si (KR);
Il-hyuk Kim, Hwaseong-si (KR);
Yeong-sik Mun, Suwon-si (KR)

(73) Assignee: **SAMSUNG ELECTRONICS CO.,
LTD.**, Suwon-si (KR)

(21) Appl. No.: **15/085,416**

(22) Filed: **Mar. 30, 2016**

(30) **Foreign Application Priority Data**

Jul. 29, 2015 (KR) 10-2015-0107416

Publication Classification

(51) **Int. Cl.**
G03G 9/097 (2006.01)
G03G 9/08 (2006.01)
(52) **U.S. Cl.**
CPC **G03G 9/09708** (2013.01); **G03G 9/0804**
(2013.01)

(57) **ABSTRACT**

Provided is a method of preparing a poly-silicic-ferric coagulant (PSFC) having a controlled aggregating strength. In particular, according to an embodiment, provided is a method of preparing a PSFC that may effectively suppress both formation of fine toner particles having a particle size that is smaller than a desired particle size and formation of coarse toner particles having a particle size that is greater than the desired particle size, wherein the PSFC for a toner is used in preparation of a toner by using an emulsion aggregation (EA) method. The PSFC for a toner prepared by using the method, according to an embodiment, significantly exhibits a controlled aggregating strength, and thus a viscosity of an emulsion aggregation solution for the toner preparation is appropriate, which results in suppressing production of fine toner particles and coarse toner particles. In this regard, a toner preparation yield may improve.